




ROLLER BEARING PUMPS AND MOTORS
SLEEVE BUSHING PUMPS AND MOTORS
FLOW DIVIDERS/INTENSIFIERS
ACCESSORIES



For mobile and industrial applications:



- Construction Equipment
- Refuse Equipment
- Mining Machinery
- Agricultural Equipment
- Oil Field Equipment
- Industrial Equipment
- Forestry Equipment






The Sensible Choice



ROLLER BEARING PUMPS AND MOTORS

Specifications

Gear Width

Series		0.50	0.75	1.00	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	
 P2100	2100/3000/3100	GPM/1000 RPM/2000 PSI	**	**	6.5	8.5	11.0	12.5	15.0				
		LPM/1000 RPM	**	**	25	32	42	47	57				
		IN³	1.0	1.5	2.0	2.5	3.0	3.5	4.00				
		CC	16.4	24.6	32.8	41.0	49.2	57.3	65.5				
		*** Max RPM	2400	2400	2400	2400	2400	2400	2400				
		# 2100 - Max PSI	3000	3000	3000	3000	3000	2500	2500				
		# 3100 - Max PSI	3000	3000	3000	3000	3000	2500	2500				
		# 3000 - Max PSI	2500	2500	2500	2500	2500	2250	2250				
		* Motor/Input GPM	**	**	12.0	14.0	16.5	19.0	21.0				
		* Motor/Output in-lbs	**	**	570	730	895	1035	1175				
		* Motor/Output HP	**	**	9.0	11.5	14.0	16.5	18.6				
 P5151	5000/5100/5151	GPM/1000 RPM/2000 PSI	**	**	9.5	12.0	14.5	17.5	19.5	21.0	23.5		
		LPM/1000 RPM	**	**	36	45	55	66	74	79	89		
		IN³	1.29	1.93	2.57	3.22	3.86	4.50	5.15	5.79	6.43		
		CC	21.1	31.6	42.2	52.7	63.2	73.8	84.3	94.9	105.4		
		+ Max RPM	2400	2400	2400	2400	2400	2400	2400	2400	2400		
		5151 - Max Peak PSI	N/A	N/A	N/A	N/A	N/A	3000	3000	3000	3000		
		# 5100 - Max PSI	3000	3000	3000	3000	3000	3000	2500	2500	2500		
		# 5000 - Max PSI	2500	2500	2500	2500	2500	2000	2000	2000	2000		
		* Motor/Input GPM	**	**	13.5	16.5	19.5	23.0	26.0	29.0	32.0		
		* Motor/Output in-lbs	**	**	725	925	1130	1320	1510	1695	1885		
		* Motor/Output HP	**	**	11.5	15.0	18.0	21.0	24.0	27.0	30.0		
 P7500	7500/7600	GPM/1000 RPM/2000 PSI	**	**	14.5	19.0	23.0	27.0	31.0	35.5	39.0	44.0	49.0
		LPM/1000 RPM	**	**	55	72	87	102	117	134	148	167	185
		IN³	2.02	3.03	4.04	5.06	6.07	7.08	8.09	9.1	10.1	11.1	12.1
		CC	33.1	49.7	66.3	82.8	99.4	116.0	132.5	149.1	165.7	182.2	198.8
		Max RPM	2400	2400	2400	2400	2400	2400	2400	2400	2400	2400	2400
		# 7600 - Max PSI	3000	3000	3000	3000	3000	3000	2500	2500	2500	2000	2000
		# 7500 - Max PSI	2500	2500	2500	2500	2500	2500	2500	2250	2250	2000	2000
		* Motor/Input GPM	**	**	23.0	28.0	33.0	37.5	42.0	46.5	51.0	56.0	61.0
		* Motor/Output in-lbs	**	**	1095	1390	1690	1980	2265	2590	2915	3300	3690
		* Motor/Output HP	**	**	17.5	22.0	27.0	31.5	36.0	41.0	46.5	52.5	58.5

*Motor Specifications are given at 1000 RPM and @ 2000 PSI

** Consult Permco on these gear sizes.

***2000 RPM Maximum on Motors

The information shown above represents the maximum continuous operating conditions.

+ Maximum 3000 RPM for 5151 series.

SLEEVE BUSHING PUMPS AND MOTORS

Specifications

Gear Width

Series		0.50	0.75	1.00	1.25	1.50	1.75	2.00	2.25	2.50
P124	GPM/1000 RPM/Rated PSI	2.0	3.5	5.0	6.0	7.5	9.0	10.0		
	LPM/1000 RPM	8	13	19	23	28	34	38		
	IN³	0.62	0.93	1.24	1.55	1.86	2.17	2.48		
	CC	10	15	20	25	30	35	40		
	Max RPM	3000	3000	3000	3000	3000	3000	3000		
	# Max PSI	3500	3500	3500	3500	3300	2900	2500		
	# Max Bar	241	241	241	241	227	200	172		
	* Motor/Input GPM	**	**	8.0	9.0	10.5	12.0	13.5		
	* Motor/Output in-lbs	**	**	660	825	930	955	945		
	* Motor/Output HP	**	**	10.5	13.0	15.0	15.0	15.0		



P124

P197 Tandem	GPM/1000 RPM/Rated PSI	**	**	7.0	9.0	11.0	13.0	15.0		
	LPM/1000 RPM	**	**	26	34	42	49	57		
	IN³	0.99	1.48	1.97	2.46	2.96	3.45	3.94		
	CC	16.1	24.2	32.3	40.4	48.4	56.5	64.6		
	Max RPM	2400	2400	2400	2400	2400	2400	2400		
	# Max PSI	**	**	4000	4000	3750	3500	3250		
	# Max Bar	**	**	276	276	259	241	224		



P197 Tandem

M257	GPM/1000 RPM/Rated PSI	**	**	9.0	12.0	14.5	17.0	19.5	22	25
	LPM/1000 RPM	**	**	34	45	55	64	74	83	95
	IN³	1.29	1.93	2.57	3.21	3.86	4.50	5.14	5.78	6.43
	CC	21.1	31.6	42.1	52.6	63.2	73.7	84.2	94.8	105.3
	Max RPM	2400	2400	2400	2400	2400	2400	2400	2400	2400
	# Max PSI	4500	4500	4500	4500	3500	3250	3000	2750	2500
	# Max Bar	310	310	310	310	241	224	207	190	172
	+ Motor/Input GPM	**	**	14.5	17.5	20.5	23.5	26.0	29.5	31.5
	+ Motor/Output in-lbs	**	**	1250	1600	1950	2150	2250	2350	2350
	+ Motor/Output HP	**	**	19.5	25.5	31.0	34.0	36.0	37.5	37.5



M257

P360 Tandem	GPM/1000 RPM/Rated PSI	**	**	12.7	16.5	20.4	24.2	28.1	31.9	35.8
	LPM/1000 RPM	**	**	48.8	63.3	77.7	92	106.6	121	135.5
	IN³	1.80	2.70	3.60	4.50	5.40	6.30	7.20	8.10	9.00
	CC	29.5	44.2	59.0	73.8	88.5	103.3	118.0	132.8	147.5
	Max RPM	2400	2400	2400	2400	2400	2400	2400	2400	2400
	# Max PSI	3500	3500	3500	3500	3500	3500	3500	3250	3000
	# Max Bar	241	241	241	241	241	241	241	224	207



P360 Tandem

*These motor specifications are given at 1000 RPM @ rated PSI.

**Consult Permco on these gear sizes.

#The information shown above represents the maximum continuous operating conditions.


+These motor specifications are given at 1000 RPM @ 3000 PSI for 1", 1.5", 1.75", and 2"; @ 2750 PSI for 2.25"; and @ 2500 PSI for 2.5"

DUMP PUMPS AND ACCESSORIES



DM-640

Pump/valve assembly for heavy and medium duty dump trucks and dump trailers



DMD-25

Series	IN ³ (CC)	GPM/900 RPM/2000 PSI	GPM/1200 RPM/2000 PSI	GPM/1500 RPM/2000 PSI
DM-512-20/DMD-20	5.12 (84.3)	17.5	24.0	30.5
DM-640-25/DMD-25	6.40 (105.4)	21.0	29.0	37.5

Permco Dump Pump Features ☒ Direct mount SAE "B" 4 bolt or twin shafted remote mount with bracket (DM-640) or built-in mounting bracket (DMR-400) ☒ Manual shift, "OEM" air shift (DM-640 and DMD-25 only), or after market air shift, each with full metering capabilities ☒ 100% factory tested ☒ Heavy duty roller bearings ☒ Pump and cylinder protected in the raise and neutral position of the spool ☒ 2 or 3 line configurations available ☒ 2 extended studs for easy installation of pump support bracket on direct mount (DMD-20 and DMD-25 only) ☒ Built-in load check maintains dump body angle and is installed in the cylinder port for superior self-cleaning ☒ Built-in direct acting relief valve set at factory ☒ Neutral lock-out safety cap for use with pull-out cable ☒ High strength alloy steel gear and shaft set



DMD-400

Pump/valve assembly for medium and light duty dump trucks



DMR-400

Series	IN ³ (CC)	GPM/900 RPM/2000 PSI	GPM/1200 RPM/2000 PSI	GPM/1500 RPM/2000 PSI
DMR/DMD-300	3.0 (49.2)	10.0	14.0	17.5
DMR/DMD-400	4.0 (65.5)	13.5	19.0	24.0

Air Shift Controls and Towers



PAVC-295-T-8

The **PAVC-295-T-8** series towers come in either an 8" or 13" tower. The PTO is kicked out of gear when the pump lever is put into the "lower" position.



PCONV-PER-4

The **PCONV-PER-4** series towers come in an 8" tower. It also comes with a PTO valve cutout for a Chelsea PTO. The air valve shown is supplied with the PTO.



P1229

The **P1229** air valve controls both the Dump Pump and the PTO in one lever. There are options for detent of the lever controlling the pump and a PTO kickout. The valve can be ordered with a bracket for installation on an air seat.

The **997-00971A** is an after market air shift cylinder that fits the DMD-25 and DM-640 Dump Pump as well as all other units of similar design.



997-00971A

GEMINI DUAL-USE PUMPS



Gemini

Gemini Dual Use Pump Features: Designed to be used with dual use applications, typically a dump trailer and a live floor or goose neck ☒ Dual pressure relief valve: low for dump trailer, high for other application, each field adjustable ☒ Direct mount SAE "B" 4 bolt or twin shafted remote mount with bracket ☒ Heavy duty roller bearings

997-01444



Series	IN ³ (CC)	GPM/900 RPM/2000 PSI	GPM/1200 RPM/2000 PSI	GPM/1500 RPM/2000 PSI	Max RPM	Max PSI
DG-20 / RG-20	5.12 (84.3)	17.5	24.0	30.5	1800	3200

The **997-01444** air tower controls the pump/valve, PTO, cylinder, and the high/low pressure setting on the relief valve for the dual pressure. Safety features include auto kickout to low pressure when PTO is disengaged and optional safety latch PTO switch with auto kickout in lower position. Other tower options available: consult factory

TWO-SPEED MOTORS



W5100
Two-Speed

The **Two-Speed Motor** has the two-speed valve built into the bearing carrier providing compact packaging and offering lower system cost by eliminating expensive external components. The two-speed can be shifted on the fly to either the low speed/high torque or high speed/low torque modes. Two-Speed Motors are ideal for winch, crawler, conveyer, auger and many other types of applications with low speed/high torque and high speed/low torque requirements. Two-Speed Motors can be constructed with our standard tooth count gears or our high tooth count winch motor gears depending on the application. In low speed/high torque applications the high tooth winch motor gears provide improved starting torque, smoother low speed operations and lower torque ripple.

VERSA-PAK/REFUSE SYSTEMS



Versa-Pak
Unloading System

The **Versa-Pak Unloading System** limits the flow to the system while in use to prevent hydraulic overspeeding. While in the off mode the flow is diverted back to the tank at low pressures to control horsepower losses. Available with optional speed sensor and digital speed controller to further protect the hydraulic system.

The **Versa-Pak Dry Valve System** incorporates an air operated dry valve which permits hydraulic operation while the vehicle is in motion. It reduces fuel consumption during the off mode and eliminates heat build-up associated with "live" systems in the on mode. Available with optional speed sensor and digital speed controller to further protect the hydraulic system.



Versa-Pak Dry Valve
System

Versa-Pak
Flow Control/Unloader System



The **Versa-Pak Flow Control/Unloader System** allows a preset amount of flow to the hydraulic system with the excess flow being returned to tank; this function protects the system's main relief valve from being flooded. In addition, the priority type pressure compensated flow control minimizes heat generation by returning unused oil back to tank at only a few hundred PSI more than system pressure.



The Sensible Choice



PermcO offers a complete line of hydraulic filters and tank strainers. Both 10 and 25 micron filter elements are available with filter heads ranging from 20 gallon with 3/4" NPT ports to 90 gallon with 1 1/2" split flange ports. 1/8" NPT gauges are optional.

PermcO's remote mounted **Relief Valve AZ5514J-100-25** or **AZ5514J-100-32** comes with 1" NPT ports. It is available with either 2500 or 3200 PSI maximum settings, and is field adjustable. It is easily mounted with 3 mounting holes and directly replaces common relief valves currently found from other manufacturers. Available in 3/4" and 1" NPT ports; 3/4" and 1" O-ring ports and available with optional pilot operated relief cartridges.



AZ5514J-100-25

PermcO offers **Port End Covers** for the P3000, P3100, P5000, and P5100 pumps which incorporate a built-in relief valve. Pressure settings are factory set at 2500 or 3200 PSI. Settings are field adjustable. The tank port on the P3000 and P3100 are either internally or externally exhausted. The P5000 and P5100 are externally exhausted only.




P5000/5100 Port End Cover with Relief Valve

Hydraulic Winch Motors are now available from PermcO. These motors are equipped with a special high tooth count gear as opposed to the traditional standard tooth count gear. This allows for better start-up torque and less "torque ripple". They are available in the W3000/3100, W5000/5100, and W7500/7600 series.



W5100



FD3000

PermcO offers a complete line of hydraulic **Flow Dividers and Intensifiers**. FD3000/3100, FD5000/5100, and FD7500/7600 are available in the roller bearing series. Input flows up to 70 GPM per section with a maximum pressure drop of 2500 PSI.

PermcO uses only the best material available in all of our parts which assures you the most reliable gear technology products available. PermcO has built a reputation on quality and service. **PermcO is The Sensible Choice.**



PermcO
1500 Frost Rd.
P. O. Box 2068
Streetsboro, OH 44241
USA

Phone 330-626-2801
Fax 330-626-2805
e-mail info@permco.com
www.permco.com

PermcO TianJin Fluidpower Mfg.
Co., Ltd
Fenghua Industrial Part
9th Avenue
TEDA, China PC: 300457

PermcO (TianJin) Hydraulics Inc., Ltd.
236 Jinbindadao Free Trade Zone
TianJin Port, China
e-mail: technic@permcotj.com
www.permcotj.com