


Heavy & Medium Duty Trucks & Trailers

DUMP PUMPS



Precision-Engineered Fluid Power Products

The Sensible Choice for Pump/Valve Assembly



Dump Trucks
Dump Trailers



Features



- Pump and cylinder protected in the "Raise" and "Neutral" position of the spool
- Manual shift, factory installed "OE" air, or "Add-on" air shifts each with full metering capabilities
- Built-in load check maintains dump body angle and is installed in the cylinder port for superior self-cleaning
- NPT & SAE ports are available
- Built-in direct acting relief valve set at factory
- 100% factory tested
- Flows of 37 and 46 GPM at 1800 RPM
- Pressures to 2500 PSI
- Speeds to 2400 RPM
- High strength alloy steel gear and shaft set
- Neutral lock-out safety cap for use with pull-out cable
- 2 line for intermittent duty or 3 line for continuous duty systems
- 2 extra long studs for easy installation of pump support bracket on direct mount
- Pressure balanced wear plates maintain high pump efficiency throughout all operating ranges
- DIN mount and shaft available







Pump/Valve Assembly

Dimensional Data (inches)



	A	B
DMD-20	16.85"	2.75"
DMD-25	17.35"	3.25"



	C	B
DM-512-20	16.35"	2.75"
DM-640-25	16.85"	3.25"



Perenco is a leading manufacturer of high-pressure hydraulic gear/vane pumps and motors, flow dividers, intensifiers, and accessories. Available in a wide variety of sizes and configurations to suit your application needs.

Dump Pumps are not recommended for ejector, conveyor, or moving floor type applications; please refer to Gemini brochure for those type or applications

Pump Code

DMD - 25 - Z - L - AS - 20 - EB

Direct Mount, SAE 4 Bolt "B"

20 2.0" Gear / 37 GPM at 1800 RPM
25 2.5" Gear / 46 GPM at 1800 RPM

X 2 Line (Without 3 Line Sleeve)
Z 3 Line (With 3 Line Sleeve)

L Left Hand Rotation
R Right Hand Rotation

Extended Stud Orientation

Delete Top Two (Std.)
EB Bottom Two
EL Left Side
ER Right Side
E4 All four

Relief Valve Setting

20 2000 PSI
25 2500 PSI

AS Air Shift
MS Manual Shift

DM-640-25-ZR - M - T - 200

Remote Mount

512-20 In.³ x 100 / 2.0" Gear / 37 GPM at 1800 RPM
640-25 In.³ x 100 / 2.5" Gear / 46 GPM at 1800 RPM

X 2 Line (Without 3 Line Sleeve)
Z 3 Line (With 3 Line Sleeve)

Valve Orientation
L Left Side
R Right Side (Std.)

Relief Valve Setting

200 2000 PSI
250 2500 PSI

T Manual Shift
AS "OE" Air Shift

M With Mounting Bracket (Std.)
O Without Mounting Bracket

**Our Online Support is available
 24/7/365 for your needs!**

Email: support@permco.com

Call: (800) 626.2801



www.permco.com



Perenco USA | 1500 Frost Road | P. O. Box 2068 | Streetsboro, Ohio 44241



NFPA
Solutions through
motion technology

